











# MALE PCB PINS

## PRINTED CIRCUIT PINS • NAIL HEAD TYPE

<p><b>5062</b> 5062-0-00-XX-00-00-33-0 Solder mount in .029 mounting hole</p> 	<p><b>8451</b> 8451-0-00-XX-00-00-33-0 Solder mount in .029 mounting hole</p> 	<p><b>6477</b> 6477-0-00-XX-00-00-38-0 Solder mount in .034 mounting hole</p> 	<p><b>4477</b> 4477-0-00-XX-00-00-33-0 Solder mount in .034 mounting hole</p> 						
<p><b>4268</b> 4268-0-00-XX-00-00-33-0 Solder mount in .039 mounting hole</p> 	<p><b>9086</b> 9086-0-00-XX-00-00-33-0 Solder mount in .040 mounting hole</p> 	<p><b>8330</b> 8330-0-00-XX-00-00-38-0 Solder mount in .044 mounting hole</p> 	<p><b>9228</b> 9228-0-00-XX-00-00-38-0 Solder mount in .044 mounting hole</p> 						
<p><b>6095</b> 6095-X-00-XX-00-00-38-0 Solder mount in .044 mounting hole</p> 	<table border="1"> <thead> <tr> <th>Basic Part Number</th> <th>Length L</th> </tr> </thead> <tbody> <tr> <td>6095-0</td> <td>.580</td> </tr> <tr> <td>6095-1</td> <td>.475</td> </tr> </tbody> </table>	Basic Part Number	Length L	6095-0	.580	6095-1	.475	<p><b>6092</b> 6092-0-00-XX-00-00-33-0 Solder mount in .044 mounting hole</p> 	
Basic Part Number	Length L								
6095-0	.580								
6095-1	.475								

### SPECIFICATIONS:

**Pin Material:** Brass Alloy 360, 1/2 Hard  
(Except where noted)

**Dimensions:** Inches

**Tolerances On:** Lengths:  $\pm .005$   
Diameters:  $\pm .002$   
Angles:  $\pm 2^\circ$



**ORDER CODE:** XXXX - X - 00 - XX - 00 - 00 - XX - 0

**BASIC PART #** →

→ **SPECIFY PIN FINISH:**

- 01 200  $\mu$ " TIN/LEAD OVER NICKEL
- ◆ 80 200  $\mu$ " TIN OVER NICKEL (RoHS)
- ◆ 15 10  $\mu$ " GOLD OVER NICKEL (RoHS)
- ◆ 21 20  $\mu$ " GOLD OVER NICKEL (RoHS)
- ◆ 34 50  $\mu$ " GOLD OVER NICKEL (RoHS)

