

Part Number: 6200FL



Product Description

Fire Alarm Cable, Plenum-FPLP, 2-16 AWG stranded bare copper conductors with Flamarrest® insulation, overall Beldfoil® shield, Flamarrest® jacket with ripcord

Technical Specifications

Product Overview

uitable Applicatio	ons:		Fire Pr	otections, Ala	arm, Signal,	Monitor/Dete	ction, Audio Circuit	s, Con	trol Circuits	, Initiating	Circuits
/sical Char	racteristi	ics (Ove	erall)								
onductor											
WG Stranding			lo. of Con	ductors							
6 19x29	BC - Bare	Copper 2	_								
onductor Count:			2	-							
onductor Size:			16 AW	G							
ulation											
Ma	aterial		Material	Trade Name	Nominal	Wall Thickne	ss				
S PVC - Low Sm	oke Polyvin	yl Chloride	Flamarre	st®	0.009 in						
lor Chart											
umber Color											
Black											
Red											
iter Shield Mate	rial										
uter Shield Mater		Aaterial Tra	ade Name	Coverage	[%] Drain	wire Material	Drainwire AWG	Drain	wire Con	struction	n x D
ype Mater			ade Name	Coverage		wire Material ïnned Copper		Drain Solid	wire Con	struction	n x D
ype Mater ape Aluminum/F	rial M Polyester E		ade Name						wire Con	struction	n x D
ype Mater ape Aluminum/f iter Jacket Mate	rial M Polyester E				TC - T	ïnned Copper	24	Solid	wire Con	struction	n x D
ype Mater ape Aluminum/F ter Jacket Mate Ma	rial N Polyester E orial aterial	3eldfoil®	Material	100 % Trade Name	TC - T	inned Copper		Solid		truction	n x D
ype Mater ape Aluminum/f ter Jacket Mate Ma	rial N Polyester E orial aterial	3eldfoil®	Material	100 % Trade Name	TC - T	inned Copper	24 ominal Wall Thick	Solid	Ripcord	struction	n x D
pe Matei pe Aluminum/f ter Jacket Mate Ma : PVC - Low Smo	rial N Polyester E nrial aterial oke Polyving	3eldfoil® yl Chloride	Material Flamarre	100 % Trade Name	TC - T	inned Copper	24 ominal Wall Thick	Solid	Ripcord	truction	n x D
ype Matei ape Aluminum/f iter Jacket Mate Ma S PVC - Low Smo	rial N Polyester E nrial aterial oke Polyving	3eldfoil® yl Chloride	Material Flamarre	100 % Trade Name	TC - T	inned Copper	24 ominal Wall Thick	Solid	Ripcord	struction	n x D
ype Matei ape Aluminum/f iter Jacket Mate S PVC - Low Sm Donstruction	rial N Polyester E nrial aterial oke Polyving	3eldfoil® yl Chloride	Material Flamarre	100 % Trade Name	TC - T	inned Copper	24 ominal Wall Thick	Solid	Ripcord	struction	n x D
ype Mater ape Aluminum/f iter Jacket Mate Ma S PVC - Low Sm construction bling	rial N Polyester E nrial aterial oke Polyving	3eldfoil® yl Chloride	Material Flamarre	100 % Trade Name	TC - T	inned Copper	24 ominal Wall Thick	Solid	Ripcord	struction	n x D
ype Mater ape Aluminum/f iter Jacket Mate Ma S PVC - Low Sm onstruction ibling Twists	rial N Polyester E nrial aterial oke Polyving	3eldfoil® yl Chloride	Material Flamarre	100 % Trade Name	TC - T	inned Copper	24 ominal Wall Thick	Solid	Ripcord	struction	n x D
ype Mater ape Aluminum/f iter Jacket Mate	rial N Polyester E nrial aterial oke Polyving	3eldfoil® yl Chloride	Material Flamarre	100 % Trade Name	TC - T	inned Copper	24 ominal Wall Thick	Solid	Ripcord	struction	n x D
ype Mater ape Aluminum/f ater Jacket Mate Ma S PVC - Low Sm Donstruction bling Twists 3 twist/ft	rial N Polyester E aterial oke Polyving and Dim	3eldfoil® yl Chloride aensions	Material Flamarre	100 % Trade Name	TC - T	inned Copper	24 ominal Wall Thick	Solid	Ripcord	struction	n x D
ype Mater ape Aluminum/f iter Jacket Mate Ma S PVC - Low Sm onstruction ibling Twists	rial N Polyester E aterial oke Polyving and Dim	3eldfoil® yl Chloride aensions	Material Flamarre	100 % Trade Name	TC - T	inned Copper	24 ominal Wall Thick	Solid	Ripcord	struction	n x D
ype Mater ape Aluminum/f Iter Jacket Mate Ma S PVC - Low Sm Onstruction Ibling Twists 3 twist/ft	rial N Polyester E aterial oke Polyving and Dim	3eldfoil® yl Chloride aensions	Material Flamarre	100 % Trade Name	TC - T	inned Copper	24 ominal Wall Thick	Solid	Ripcord	truction	nxD
ype Mater ape Aluminum/f ater Jacket Mate Ma S PVC - Low Sm onstruction onstruction bling Twists 3 twist/ft ectrical Cha	rial N Polyester E aterial aterial woke Polyving and Dim	3eldfoil® yl Chloride aensions	Material Flamarre	100 % Trade Name st®	TC - T	inned Copper	24 ominal Wall Thick	Solid	Ripcord	struction	nxD
ype Mater ape Aluminum/f Iter Jacket Mate Mater S PVC - Low Sm Onstruction obling Twists 3 twist/ft ectrical Cha	rial N Polyester E arial aterial oke Polyviny and Dim	3eldfoil® yl Chloride aensions	Material Flamarre	100 % Trade Name st®	TC - T	inned Copper	24 ominal Wall Thick	Solid	Ripcord	struction	nxD

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
78 pF/ft	140.5 pF/ft

Current

Max. Recommended Current [A]

11 Amps per conductor @ 25°C A

Voltage

UL Voltage Rating 300 V RMS

Temperature Range

UL Temp Rating:	75°C
Operating Temp Range:	0°C To +75°C

Mechanical Characteristics

Bulk Cable Weight: 2	26 lbs/1000ft
Max Recommended Pulling Tension: 6	61 lbs
Min Bend Radius/Minor Axis: 1	1.875 in

Standards

NEC Articles:	760
NEC/(UL) Specification:	FPLP

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2009-10-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL voltage rating: 300 V RMS	UL Flammability:	NFPA 262 Plenum Flame Test (UL910)
	UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	Yes
Part Number	

Part Number

Non-Plenum Number:	5200FL
Non-Plenum Number:	5200FL

Variants

 Item #
 Color

 6200FL 0021000
 Red

 6200FL 002U1000
 Red

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.